

# *Knox Concert Series*

P O Box 2501, Anniston, AL 36202 [knoxconcert@cableone.net](mailto:knoxconcert@cableone.net)

## The Knox Concert Series (KCS) / Anniston Performing Arts Center (APAC) **Technical Specifications**

### **I. Lighting System**

#### **A. Control System**

1. ETC Element 40/250 Control Console. The console has the latest software and dual monitors. The console is setup to use the iRFR or aRFR remotes.
2. House light dimmer control is new with control stations on both sides of stage, the light booth, and the main entrance. All houselights are dimmable LED.

#### **B. Dimming Systems**

1. ETC Sensor + Dimmer System w/126 dimmers.
2. ETC Smartpack Touring Dimmer System with 481.2K dimmers to socopex outputs.
3. Dimmer system is DMX controllable with 1 DMX channel hardwired to the rack and an additional DMX line to SR to the Smartpack.
4. Dimmers are set up in a dimmer-per-circuit system.

#### **C. Instrumentation**

1. 24 – FOH, 19 degree ETC S4 Ellipsoidal Spotlights with 750W lamps.
2. 12 – ETC S4 26 degree Ellipsoidal Spotlights with 575W lamps.
3. 12 – ETC S4 36 degree Ellipsoidal Spotlights with 575W lamps.
4. 24 ETC S4jr 36 degree Ellipsoidal Spotlights with 575W lamps.
5. 16 – ETC S4 Fresnels with 750W lamps.
6. 42 ETC S4 PAR's with 575W lamps.
7. 6 Altman 3 cell Sky Cycs with 1000 watt lamps.
8. 2 Strong Radiance Long Throw Follow Spots located in the Lighting/Sound Booth.

#### **D. Hanging Positions**

# *Knox Concert Series*

FOH #1 Catwalk with 24 circuits 55 feet from plaster line.

1st Electric, 40' 12X12 truss 6' down stage of plaster line, on 2 -1 ton chain motors. 18 circuits in 3 pigtail boxes.

2nd Electric 15 circuits, 2'-6" US from plaster line.□

3rd Electric 16 circuits, 9'-0" US from plaster line.□

4th Electric 14 circuits, 13'-0" US from plaster line.□

6 - 12' Portable Steel tower trusses on deck for side lighting.

## **II. Sound System**

### ***A. Front of House***

1. Yamaha MG 24/14FX Mixing Console.

2. Dual DJ style CD Player.

3. Clear-Com Intercom System, 2 channel with 6 single channel belt packs and 7 headsets.

### ***B. Amp Rack***

1.3 - Yamaha PC9501N Stereo Amplifiers.

2. dBx Driverack 260.

3. A Stage Listen System that feed speakers in the dressing room area.

### ***C. Loudspeaker Systems***

1. Left/Right Yamaha IF 2115/AS Speakers and 4 Yamaha IF 2208 delay speakers. FOH is setup stereo.

2. There are 2 independent monitor feeds to stage

3. The 4 floor monitors are Yamaha IF 2208. All speakers are equipped with speakon connectors.

**III. Additional Production Provisions of KCS as Provided by Chevalier Productions, LLC - follows: NOTE: KCS/APAC and Chevalier production packages are the technical setup Knox provides.**

# Chevalier Productions, LLC

Audio\*Lighting\*Backline\*Staging\*Video\*Crew

Additional Production Provisions of KCS, as Provided by Chevalier Productions, LLC;  
***KCS/APAC and Chevalier production packages are the technical setup Knox provides.***

## Audio System

JBL VERTEC 4888

House Console: Avid SC 48

House Effects: Processing in console

House Drive: Lake

- (1) CDR
- (2) ClearCom
- (3) Computer

## House Cabinets:

- ( 12) JBL VERTEC 4888 3 WAY MAINS
- (4) JBL VERTEC 4880 SUBS

House Power: Lab Gruppen

Monitor Console: Avid SC 48

Monitor EQ:

## Monitor Cabinets:

- (12) JBL 712 M ( Bi – amped wedges)
- (2) JBL SR 4722 ( Side fills)
- (1) JBL SRX 4719 (Drum sub)

## Monitor Power:

- Bi- amped Racks
- (6) LAB GRUPPEN PLM 10 K

Snake System: Ramtech 54 Channel

Updated: Aug. 2017

Page 3 of 10

# Chevalier Productions, LLC

Audio\*Lighting\*Backline\*Staging\*Video\*Crew

AC Distro: 200 Amp 120/240 (20) Circuits

Mics: Microphone package and all cabling

Lighting Rig: 80 FEET OF TRUSS

Control: Hog 4

Dimming:

Fixtures: MARTIN MAC AURA (12)  
ELATION FUZE 350 Z (12)  
( 2 ) BANK OF 8 LIGHT MOLE'S  
( 1 ) MARTIN HAZER  
(12) MARTIM QUANTUM PROFILE  
(6) Elation 5 R Beams

Power: Distro with tails

COM: Clear Com to all stations needed

Cabling: 250 of Control

Gel assortment

# Knox Concert Series

## IV. Stage

1. The stage floor is 52' wide at the proscenium and 28' deep from curtain line to back wall. The stage floor is a sprung dance floor with 3/4" plywood and 3/4" T&G pine floor painted black. There is no crossover except a 3' space behind the last curtain.
2. There is an 8' removable thrust covering the orchestra pit. The pit is 12' X 24' with a fixed height and a floor level covering. The pit takes about 4-6 hours to set up, use of the pit must be communicated early.
3. The grid is 54' high and the proscenium arch is 18'. The walkable grid only covers the first 7 feet upstage of proscenium.
4. The SL wing is 26' wide and the SR wing is 13'-6" wide.
5. The fly system is a wire-guided manual counterweight system with 3 single purchase electrics and 11 double purchase scenery lines. The fly rail is located SR at 18' above the stage floor. There is a new loading rail. The double purchase line sets are limited to 850 lbs. on the pipe. We currently have 8,000 lbs. of stage weights.
6. House soft goods include a White Cyc, a full stage black, a black scrim, and three sets of black legs and borders.
7. The Blue Main Curtain is dead hung on a traveler, downstage of the proscenium.
8. There is a 5'6" wide X 9'10" tall double door SR that leads from the outside loading dock to the SR apron. There is also a street level ramp leading up to the loading dock.
9. There is a 400 amp switch and a 225 amp switch SL and a 200 amp switch SR.
10. Knox now owns a 48' wide by 32' deep Black/Grey Dance Floor.

## V. Dressing Rooms

- 1.6 – Six person dressing rooms are located in the lower level and are accessible from an USL door. There is also a large 20' X 20' room that can be used as a Greenroom or additional dressing room.
2. There are no washers or dryers on site.
- 3.2 - Jiffy Steamers

# Knox Concert Series

4.2 - Irons and ironing boards.

5.1 changing room with 5 showers connected to main dressing area. Additionally, there are 2 large locker rooms with 2 bathrooms available after 3pm for weekday performances or anytime for weekend performances. Check with the TD if interested.

6. There is one restroom with sink and commode in main dressing room area. There are large male and female restrooms with sinks and commodes up steps from rear of dressing room area. These larger restrooms are available until 5:30 p.m. As these restrooms are adjacent to the main lobby of the venue, they become public restrooms during the performance.

## VI. Additional Information

1. Trucks - Trucks may not back up to the loading dock until after 8:30am except on weekends. They must be moved to their final parking location by 2:30 PM. Our truck dock is the handicapped entrance during the show so it must be kept clear. Trucks will be required to park in a remote parking lot within four blocks of the venue.

2. Wardrobe - Wardrobe cases push around to side of theatre into dressing room area from a back door.

3. FOH Console Positions-sound and lighting positions: Rear of theatre HL and HR. Approximately a 90-foot distance. No permanent seats may be removed or positions located in center of theatre.

4. Foodservice: No cooking facilities are available in the building. If the show is using the Green Room for wardrobe, another place must be found to feed cast and crew.

5. No dedicated Production Room available. (Usually a dressing room or other area can be set up to suffice.)

6. No Telephone or Internet Service available. (We use wireless devices.)


# **Knox Concert Series**

## **Knox Concert Series (KCS)/Anniston Performing Arts Center (APAC)**

### **Venue Rules**


1. Immediately before the concert, Chairman will welcome audience and thank sponsors. This should take no more than four minutes.
2. Request brief (15 -- 20 minute) meet/greet and photo opportunity with Artist either before or immediately after concert for maximum 35 – 40 guests / 8 -10 photos.
3. Doors must open Sixty (60) minutes before performance. Seventy--five (75) if concert is season finale. Please plan all pre--concert production activities to accommodate. If piano needs to be tuned after a rehearsal, an additional 30 minutes will be required.
4. No alcohol on site / Alabama State Law.
5. No cooking on site.
6. No food or drink on auditorium floor or any seating area in the auditorium. Food and drink is allowed on stage and stage areas.
7. Shore power is not available.
8. Sound level will be controlled by KCS. The venue is relatively small but acoustically excellent. Please have your Tech. Personnel discuss this with KCS personnel well before the concert date so that audio equipment list can be reviewed and that only equipment that is appropriate for the venue be used.
9. Internet DSL/ WIFI, phone line are not available (use wireless devices).
10. A specific production office is not available. Usually a dressing room or other area can be set up to suffice.
11. Forklift and truck ramps are not available; generally, not needed. Dock height is at stage level.
12. No on--stage storage. Equipment cases must be reloaded to truck and moved away from the loading dock before performance.
13. Trucks cannot remain at the loading dock because this area also serves as our handicapped entrance. Trucks must be moved to a remote parking lot, which is within a four--block radius of the venue. Driver shuttle will be provided if necessary.

# Knox Concert Series





# Knox Concert Series



# Knox Concert Series

